



TECHNICAL DATASHEET

CORATREND primer

| | |
|------------------|--|
| Product: | GreenTherm CORATREND primer |
| Supplier: | Greenspan System Sales Ireland Ltd. Ballyhahill, Co. Limerick, Ireland, Tel: 069 82222, Email: sales@greenspan.ie |
| Size, packaging: | 16 liter / plastic pail |
| Application: | Very thin primer with good coverage in accordance with the colours of Coratrend system for the equal absorption and the enhanced adherence of the base coat, under Coratrend acrylic renders and granular marble plasters. |
| Material: | Ready to use primer based on a mixture of synthetic acrylic resin, aggregates, pigments and water. |

| Properties | Relevant standards | Technical data |
|--|-------------------------------|-------------------------------|
| Quantity | Manufacturer's declared value | 16 liter / plastic pail |
| Density | MSZ ISO 2811:1990 | 1,305-1,443 g/cm ³ |
| Coverage | Manufacturer's declared value | 1,5-2 dl/m ² |
| Drying time (on the surface) | MSZ ISO 1517:1993 | max. 2 hours |
| Drying time (in full thickness) | MSZ ISO 9117:1993 | max. 8 hours |
| Dry matter content | ÉMI HSZ 60:2004 | 54,7 - 60,4 % |
| pH value | MSZ ISO 787-9:1993 | 8,9 |
| Adhesive strength (on cement-bonded particle boards) | MSZ EN ISO 4624:2003 | 1,4 N/mm ² |

Storage and handling

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources. Storing temperature is between (+)5°C and (+)25°C, in closed plastic pail. In case of the prescribed storage and handling conditions, the expiry date of the product is 12 months after production.

Guarantee, warranty

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

Standards, specifications

ETAG 004, A-80/2007 ÉME, Application guidance of Thermomaster A-02 ETICS (Masterplast Group Zrt.)

Health and safety

In accordance with the relevant Safety Data Sheet: BA_Coratrend.Alapozó-01012010_HU

This datasheet corresponds the current knowledge on the subject, but may be revised as new knowledge and/or experience becomes available. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

***This technical datasheet is applied to products sold by Greenspan, after 01st January 2010. and valid until withdrawal or until modification.**

Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com.

*Issued: 01. 01. 2010.